



SCP 012-108 DIN is a series of piston pumps with a fixed displacement for demanding mobile hydraulics.

SCP 012-108 DIN covers the entire displacement range 12-108 cm³/rev. at a maximum working pressure of 400 bar. It is a modern, compact pump which meets the market's high demands on flow performance, pressure, efficiency and small installation dimensions.

It is either mounted directly on the power take-off, or on a frame bracket via an intermediate shaft.

Other advantages:

- High maximum speed while maintaining low noise levels
- Smooth operation over the entire speed range
- Long life due to high demands on material selection, such as bearings, seals, etc.
- O-rings on all contact surfaces as well as double shaft seals eliminate oil leakage from the pump and power take-off
- The stop shoulder on the angular housing allows the pump's direction of rotation to be changed without the risk of altering the gear meshing

Versions, main data

Example

SC	P	-	084	L	-	N	-	DL4	-	L35	-	S0	S	-	0	00
Line	1		2	3		4		5		6		7	8		9	10

Line	SC	Sunfab Compact, bent-axis design
------	----	----------------------------------

7. Connection cover	S0	40° Sunfab standard
---------------------	----	---------------------

1. Type	P	Pump
---------	---	------

8. Connections	S	Sunfab standard
----------------	---	-----------------

2. Displacement	012	017	025	034	040	047	056	064	084	108
-----------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

9. Additional	0	-
---------------	---	---

3. Direction of rotation	R	Right
	L	Left


10. Accessories	00	No accessories available
-----------------	----	--------------------------

4. Shaft seal	N	Nitrile
---------------	---	---------

5. Mounting flange	DL4	DIN 4-h (ISO 7653D)
--------------------	-----	---------------------

6. Shaft	L35	DIN 5462 / ISO 14
	H35	DIN 5462 / ISO 14 Ø 8.15

SCP 012-108 DIN		012	017	025	034	040	047	056	064	084	108	
		l/min										
	rpm	500	6	9	13	17	21	24	28	32	42	54
		1000	13	17	25	34	41	47	57	64	84	108
		1500	19	26	38	51	62	71	85	95	125	162
Displacement	cm ³ /rev	12.6	17.0	25.4	34.2	41.2	47.1	56.7	63.5	83.6	108.0	
Max pump speed												
<i>continuous</i>	rpm	2300	2300	2300	2300	1900	1900	1900	1900	1500	1500	
<i>intermittent</i>		3000	3000	3000	3000	2500	2500	2500	2500	2000	2000	
Max working pressure	bar	400	400	400	400	400	400	400	400	400	400	
Weight	kg	8.3	8.3	8.5	8.5	11.7	11.7	11.7	11.7	17.0	17.0	
Dimensions	mm	A	97	97	97	97	113	113	113	113	123	123
		B	112	112	112	112	130	130	130	130	147	147
		C	202	202	202	202	228	228	228	228	259	259
		D	99	99	99	99	109	109	109	109	126	126
		E	97	97	97	97	109	109	109	109	126	126
		F	89	89	89	89	99	99	99	99	115	115
		G	97	97	97	97	106	106	106	106	123	123
	ISO G	P	34	34	34	34	34	34	34	34	1	1
	ISO G	Q	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
Tare-weight torque (M)	Nm	6.9	6.9	7.4	7.4	13	13	13	13	21	21	
Direction of rotation	Left (L) or Right (R)											





WARNING!

When the pump is running:

1. Do not touch the pressure hose
2. Watch out for rotating parts
3. The pump and hoses may be hot

Sunfab reserves the right to make changes in design and dimensions without notice. Printing and typesetting errors reserved.

© Copyright 2022 Sunfab Hydraulics AB. All Rights Reserved.